

FP89-ME TopTech ME Ultra-Low Refrigerated / Heating Circulator

The Ultra-Low Refrigerated Circulators of the TopTech Series are equipped with a dual-stage cascade refrigeration system for continuous operation of internal and external temperature applications.

Models with ME circulator

- Heated bath cover plate to prevent condensation or ice build-up
- Pressure pump up to 0.45 bar, electronically adjustable in steps
- ACC Active Cooling Control across the entire temperature range
- Compact design Note: FP models feature an energy-saving proportional cooling control.

Product features

- PID3 cascade temperature control
- RS232 interface for online communication
- Integrated programmer for 10 program steps
- VFD COMFORT DISPLAY
- Keypad for setpoints, warning/safety values and menu functions
- ATC3 3-Point-Calibration
- Pt100 External sensor connection for measurement and control
- SMART PUMP, electronically adjustable pump stages
- Adjustable high temperature cut-out, visible via display
- Active Cooling Control
- Unique early warning system for low liquid level



Performance values

230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F)	
Heating capacity kW	1.2
Viscosity max. cSt	50
Pump capacity flow rate l/min	11 ... 16
Pump capacity flow pressure psi	3.3 ... 6.5
Power consumption A	16

Order No.	9162689.03					
Cooling capacity (Ethanol)						
°C	20	0	-20	-40	-60	-80
kW ¹	1	0.92	0.88	0.75	0.58	0.1
Refrigerant stage 1			Refrigerant stage 2			
Refrigerant	R404A		Refrigerant	R23		
Filling weight g	500		Filling weight g	200		
Global Warming Potential for R404A	3922		Global Warming Potential for R23	14800		
Carbon dioxide equivalent t	1.961		Carbon dioxide equivalent t	2.96		

¹ Performance specifications measured in accordance with DIN 12876. Cooling capacities up to 20 °C measured with ethanol; over 20 °C with thermal oil unless otherwise specified. Performance specifications apply at an ambient temperature of 20 °C. Performance values may differ with other bath fluids.

Technical data

Available voltage versions		Cooling	
Order No.	9 162 689	Cooling of compressor	2-stage Air
Available voltage versions:			
9162689.03	230V/50Hz (Schuko Plug - CEE 7/4 Plug Type F) (R404A)		
9162689.13	230V/60Hz (Nema N6-20 Plug) (R404A)		
Bath		Other	
Bath tank	Stainless steel	Classification	Classification III (FL)
Bath cover	integrated	IP Code	IP 21
Usable bath opening in. (W x L / D)	5.1 x 5.9 / 6.3	Pump type	Immersion Pump
Electronics		Dimensions and volumes	
Interfaces	Alarm output, RS232	Weight lbs	302
External pt100 sensor connection	integrated	Barbed fittings inner diameter mm	8/12 mm
Integrated programmer	1x10 steps	Dimensions in. (W x L x H)	21.7 x 23.6 x 35.4
Temperature control	PID3	Filling volume l	5.5 ... 8
Absolute temperature calibration	3 Point Calibration	Pump connections	M16x1 male
Temperature display	VFD		
Temperature setting	Keypad		
Temperature values		Included in delivery	
Setting the resolution of the temperature display °C	0.01	2 Barbed fittings for tubing 8 and 12 mm ID. (Pump connections M16x1 male)	
Working temperature range °C	-90 ... +100		
Temperature stability °C	±0.02		
Ambient temperature °C	+5 ... +40		
Setting the resolution of the temperature display °C	0.01		

All Benefits

- | | | | |
|--|--|--|---|
| | <p>For flammable bath fluid
Classification III (FL) according to DIN 12876-1</p> | | <p>ATC3. Calibration.
'Absolute Temperature Calibration' for compensating a physically caused temperature difference, 3-point calibration.</p> |
| | <p>100 % Cooling capacity
'Active Cooling Control' for cooling available throughout the entire working temperature range, fast cool-down even at higher temperatures</p> | | <p>Early warning system for high/low temperature limits
Maximum safety for applications, optical and audible alarm, convertible to automated cut-off function</p> |
| | <p>Energy saving cooling
Proportional cooling control for automatic adjustment of cooling power or temporary switch-off of compressor as needed to save up to 90 % energy in comparison to unregulated cooling machines</p> | | <p>For higher demands
PID Temperature control with drift compensation and adjustable parameters, improved temperature stability for external applications, temperature stability ± 0.01 °C internal, $< \pm 0.1$ °C external.</p> |
| | <p>Clever pump system
Reliable and consistent pump capacity, electronically adjustable pump stages</p> | | <p>Control of the external application
External Pt100 sensor connection for precise measurement and control directly in the external application</p> |
| | <p>100% Checked.
100% testing. 100% quality. Each JULABO Circulator undergoes thorough quality testing before leaving the factory.</p> | | <p>Green technology.
Development consistently applied environmentally friendly materials and technologies.</p> |
| | <p>JULABO. Quality.
Highest standards of quality for a long product life.</p> | | <p>Quick start.
Individual JULABO consultation and comprehensive manuals at your disposal.</p> |
| | <p>Satisfied customers.
11 subsidiaries and more than 100 partners worldwide guarantee fast and qualified JULABO support.</p> | | <p>Services 24/7.
Around the clock availability. You can find suitable accessories, data sheets, manuals, case studies, and more at www.julabo.com.</p> |