

# BLADE MICROMETERS

- Meet DIN863-3
- Measure the groove diameter of shafts and keyways
- Graduation 0.01mm
- Non-rotating spindle
- Ratchet stop
- Supplied with setting standards (except 0-25mm)



NON-ROTATING  
SPINDLE

3232-25A

Code	Range	Type	Accuracy	L	b
3232-25A	0-25mm	A	4μm	57	32
3232-50A	25-50mm	A	4μm	82	44.5
3232-75A	50-75mm	A	5μm	107	57
3232-100A	75-100mm	A	5μm	132.6	69.5
3232-125A	100-125mm	A	6μm	158	82
3232-150A	125-150mm	A	6μm	183.4	94.5
3232-175A	150-175mm	A	7μm	208.8	107
3232-200A	175-200mm	A	7μm	234.2	129.6
3232-225A	200-225mm	A	8μm	259.6	142.3
3232-250A	225-250mm	A	8μm	285	155
3232-275A	250-275mm	A	9μm	310.4	167.7
3232-300A	275-300mm	A	9μm	336.5	177.8
3232-25BA	0-25mm	B	4μm	57	32
3232-50BA	25-50mm	B	4μm	82	44.5
3232-75BA	50-75mm	B	5μm	107	57
3232-100BA	75-100mm	B	5μm	132.6	69.5
3232-125BA	100-125mm	B	6μm	158	82
3232-150BA	125-150mm	B	6μm	183.4	94.5
3232-175BA	150-175mm	B	7μm	208.8	107
3232-200BA	175-200mm	B	7μm	234.2	129.6
3232-225BA	200-225mm	B	8μm	259.6	142.3
3232-250BA	225-250mm	B	8μm	285	155
3232-275BA	250-275mm	B	9μm	310.4	167.7
3232-300BA	275-300mm	B	9μm	336.5	177.8

