



Specification

Model	SH-HD-900H
Type	Horizontal Type
Dimension Internal	740×600×730 (W×D×H)
Dimension External	900×930×1855
Control System	Microprocessor LCD Digital Controller
Main Filter	Hepa Filter 0.3μ 99.97% Efficiency Filter
Material Internal	Stainless Steel SUS 304 with Hair Line Finished
Material External	Steel Plate SS 41 with Power Heating Coated
Working table	Stainless Steel SUS 304 with Polishing Finished
Illumination FL Lamp	32W×2EA
UV Lamp	36W×2EA
UV Time Range	00.00 to 99HR 59 MIN (MIN SEC) Selectable LCD Counter
Winding Velocity	0.3~0.5M/SEC , 10Step Adjustable
Purity	Below to Class 100
Door Type	Tempered Glass by Weight Balance
Power	220V Single Phase

Feature

Auto Self Testing
 As Clean Bench has self-diagnosis function, Artificial Intelligence can discriminate the irregularities.

Speed Adjustable
 Clean Bench can adjust working wind speed up to 10Step.

Microprocessor LCD Control System
 As SH-HCB1 is equipped with Microprocessor LCD Digital Controller, user can realize going state of the work.

User can confirl going state of the work even in dark place owing to Back Light LCD Display.

Auto Time Safety Device
 UV Lamp will be operated according to the setting time during UV Lamp usage.

As Main/Pre Filter replacement timing is appeared in alarm sound and LCD Screen, user can realize Filter replacement timing. Thus it has user convenience and safety.

Option