



IGM technology guides you where to measure



Verify amperage measurements

FLIR CM174

Imaging 600A AC/DC Clamp Meter with IGM™

The FLIR CM174 Imaging 600A AC/DC Clamp Meter with IGM is the first clamp meter equipped with a built-in thermal imager that can quickly lead you to problems you can't see with a standard clamp meter. Featuring Infrared Guided Measurement (IGM) technology, the CM174 visually guides you to the precise location of a potential electrical problem, identifying dangerous and unknown problem areas safely. Confirm your findings with accurate amperage and voltage measurements, and center-point temperature readings. The narrow jaw enables greater accessibility, and its compact form-factor fits easily into your back pocket – so you can have thermal imaging at your fingertips everywhere you go. The FLIR CM174 will quickly become your primary electrical troubleshooting tool.

Find problems faster with IGM.

Visually identify electrical issues with the first thermal imaging clamp meter

- Conquer cluttered wires and cables IGM can quickly guide you in the right direction
- All-in-one tool carry just one device and always have access to thermal imaging
- Work safely scan a panel or cabinet for hazards using IGM without direct contact

Confirm your findings.

Verify problems, check load, and validate hot spots

- Center-point temperature to confirm hot spot
- Amperage and voltage measurements to check the load
- Laser and crosshair pinpoint the location of the problem found in thermal image

Solve complex electrical issues.

Design and functionality vital to professionals

- Narrow jaw and built-in worklights help you access difficult locations with lighting issues
- Advanced electrical features: True RMS, LoZ, VFD Mode, Inrush, Smart Diode with Disable
- Expandable to 3000 Amps AC with FLIR flex accessories



Specifications

| FLIR CM174: Imaging Clamp Mete | er | |
|------------------------------------|---|----------------|
| Imaging Detector | FLIR Lepton® microbolometer | |
| Thermal Image Resolution | 4800 pixels (60 × 80) | |
| Thermal Sensitivity | 150 mK | |
| Field of View (V x H) | 38.6° × 50.0° | |
| Color Palettes | Iron, Rainbow, Grayscale | |
| Image Frame Rate | 9Hz | |
| Temperature Measurement | Center point of thermal image | |
| Temperature Range | -13°F to 302°F (-25°C to 150°C) | |
| Temperature Distance to Spot Ratio | 30:1 | |
| Temperature Accuracy | ±5.4°F (3°C) or ±3% of rdg | |
| Spectral Response | 8 to 14µm | |
| Temperature Targeting | Class 1 Laser Pointer and Crosshair on display | |
| Emissivity Settings | 4 Presets with Custom Adjustment | |
| Electrical Measurements | Range | Basic Accuracy |
| AC/DC Voltage | 1000V | ±1.0% |
| VFD AC Voltage | 1000V | ±1.0% |
| LoZ Mode AC Voltage | 1000V | ±1.0% |
| LoZ Mode DC Voltage | 1000V | ±1.0% |
| DC Current | 600.0A | ±2.0% |
| AC Current | 600.0A | ±2.0% |
| VFD AC Current | 600.0A | ±2.0% |
| Inrush AC Current | 600.0A | ±3.0% |
| Inrush AC Current Threshold | Min 0.5A Integration Time 100ms | |
| Frequency | 60.00kHz | ±0.1% |
| Resistance | 6000Ω | ±1.0% |
| Continuity | 600.0Ω | ±1.0% |
| Capacitance | 1000μF | ±1.0% |
| Diode | 1.5V | ±1.5% |
| General information | | |
| Display | 6000 Count 2.0" (50mm) Color TFT | |
| Drop Test | 2m | |
| Jaw Opening | 1.38" (35mm), 1250MCM | |
| Category Rating | CAT IV-600V, CAT III-1000V | |
| Certifications | UL, CE, RCM and KC | |
| Battery Type | 4 x AAA | |
| Warranty | 10 Years on Product and Detector* | |
| Includes | Clamp Meter, 4 x AAA Batteries, Premium Silicone Test Leads, Quick Start, User Manual (CD), Extended Warranty Registration Card | |









-Test Leads Input

| Ordering Information | UPC | EAN |
|--|--------------|---------------|
| FLIR CM174 Imaging 600A AC/DC Clamp Meter with IGM™ | 793950371749 | 0793950371749 |
| FLIR TA72 Universal Flex Current Probe Accessory 10"(25cm) | 793950377727 | 0793950377727 |
| FLIR TA74 Universal Flex Current Probe Accessory 18"(45cm) | 793950377741 | 0793950377741 |
| FLIR TA15 Soft Sided Carrying Case | 793950377154 | 0793950377154 |
| FLIR TA55 Line Splitter | 793950377550 | 0793950377550 |
| FLIR TA52 Magnet Mount | 793950377529 | 0793950377529 |
| FLIR TA42 Belt Clip | 793950374207 | 0793950374207 |
| FLIR TA80 Premium Silicone Test Leads | 793950377802 | 0793950377802 |
| FLIR TA70 Alligator Clips | 793950377703 | 0793950377703 |



USA-NASHUA

FLIR Systems, Inc. 9 Townsend West Nashua, NH 03063 USA PH: +1 866.477.3687 USA-PORTLAND Corporate Headquarters FLIR Systems, Inc. 27700 SW Parkway Ave. Wilsonville, OR 97070 USA PH: +1 866.477.3687

EUROPE

FLIR Systems Luxemburgstraat 2 2321 Meer Belgium PH:+32 (0) 3665 5100

www.flir.com NASDAQ: FLIR

UNITED KINGDOM

FLIR Systems UK 2 Kings Hill Av. - Kings Hill West Malling Kent ME19 4AQ United Kingdom Tel.: +44 (0)1732 220 011 Fax: +44 (0)1732 843 707 $\hbox{E-mail:flir@flir.com}$

Equipment described herein may require US Government authorization for export purposes. Diversion contrary to US law is prohibited. Imagery for illustration purposes only. Specifications are subject to change without notice. ©2015 FLIR Systems, Inc. All rights reserved. (Updated 08/22/17)

