

Lowpass Filter Operating From DC to 3 GHz With SMA Female Connectors

The FMFL025 is a Five section Low pass filter. The pass band is 3000 MHz wide, from 0 to 3000 MHz with excellent rejection of 50 dB at 6000 MHz. It has a maximum insertion loss of 1 dB. The FMFL025 has SMA female connectors and is rated to 10 watts.

Electrical Specifications*

Description	Min	Тур	Max	Units
Passband Freq.	DC		3	GHz
Useable Freq. Range		DC to 3		GHz
Impedance		50		Ohms
Insertion Loss			1	dB
Passband VSWR			1.5:1	
Input Power			10	Watts
Rejection at 4.5 GHz	40			dB
Rejection at 6 GHz	60			dB

Mechanical Specifications

Size		
Length	1.1 in [27.94 mm]	
Width	0.75 in [19.05 mm]
Height	0.65 in [16.51 mm]

Connectors

Description	Connector 1	Connector 2	
Туре	SMA Female	SMA Female	

Compliance Certifications (see product page for current document)

Plotted and Other Data

Notes:

• Values at 25 °C, sea level



DC to 3000MHz D.C. 1613

DATA SHEET

FMFL025

Features:

- Design: Low Pass Filter
- Number of Sections: 5
- Connector 1: SMA Female
- Connector 2: SMA Female

Fairview Microwave 1130 Junction Dr. #100 Allen, TX 75013 Tel: 1-800-715-4396 / (972) 649-6678 Fax: (972) 649-6689 www.fairviewmicrowave.com sales@fairviewmicrowave.com






Lowpass Filter Operating From DC to 3 GHz With SMA Female Connectors from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: Lowpass Filter Operating From DC to 3 GHz With SMA Female Connectors FMFL025


URL: https://www.fairviewmicrowave.com/low-pass-filter-dc-3-ghz-sma-female-connectors-fmfl025-p.aspx



1130 Junction Dr. #100 Allen, TX 75013 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689







FAIRVIEW MICROWAVE INC.	NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].					
Lowpass Filter Operating From DC to 3 GHz With SMA Female Connectors	DWG NO FMFL025			CAGE CODE 3FKR5		
	CAD FILE 042617	SHEET	SCAL	E N/A	SIZE A	2233

1130 Junction Dr. #100 Allen, TX 75013 | Tel: 1-800-715-4396 / (972) 649-6678 / Fax: (972) 649-6689