

**N Directional Coupler 10 dB Coupled Port From 4 GHz to 8 GHz Rated To 50 Watts**

Directional couplers are indispensable components for isolating, separating and combining signals. For example, they provide a simple way of sampling microwave signals. They also can make accurate attenuator measurements since reflections are eliminated. The MC4052-10 is a 10 dB directional coupler that operates from 4 GHz to 8 GHz with 17 dB directivity minimum and can handle up to 50 Watts of CW power. The package interface has type N inputs on all of the ports.

The MC4052-10 is part of Fairview Microwave's family of directional/dual-directional couplers that offer coupling ratio up to 50 dB with excellent performance featuring high directivity, low insertion loss and VSWR. They are available in both narrow and broad bandwidths and can be used in a wide variety of applications including signal sampling, VSWR measurements, power combining and distribution.



**Features:**

- Directional Coupler
- 4 GHz to 8 GHz Frequency Range
- Coupling 10±1.5 dB
- Directivity > 17 dB
- Max Power 50W (CW)

**Applications:**

- Test and Measurement
- Military Communications
- Commercial Communications
- Wireless Communications
- SATCOM

**Electrical Specifications**

Description	Min	Typ	Max	Units
Frequency Range	4		8	GHz
Impedance		50		Ohms
Coupling		10 ±1.5		dB
Freq. Sensitivity		±0.85		dB
Insertion Loss			1.8	dB
Directivity	17			dB
Main Line VSWR			1.5:1	
Sec. Line VSWR			1.5:1	
Input Power (CW)			50	Watts
Reverse Power (CW)			5	Watts
Input Power (Peak)			3	KWatts

Electrical Specification Notes:  
 Values specified at +25°C, sea level.

**Mechanical Specifications**

<b>Size</b>	
Length	1.9 in [48.26 mm]
Width/Dia.	1 in [25.4 mm]
Height	1 in [25.4 mm]
Weight	0.317 lbs [143.79 g]

<b>Configuration</b>	
Input Connector	N Female
Output Connector	N Female
Coupled Connectors	N Female


**Compliance Certifications** (see [product page](#) for current document)

**Plotted and Other Data**

Notes:

Fairview Microwave  
 1130 Junction Dr. #100  
 Allen, TX 75013  
 Tel: 1-800-715-4396 / (972) 649-6678  
 Fax: (972) 649-6689  
[www.fairviewmicrowave.com](http://www.fairviewmicrowave.com)  
[sales@fairviewmicrowave.com](mailto:sales@fairviewmicrowave.com)

**Typical Performance Data**




N Directional Coupler 10 dB Coupled Port From 4 GHz to 8 GHz Rated To 50 Watts from Fairview Microwave is in-stock and available to ship same-day. All of our RF/microwave products are available off-the-shelf from our ISO 9001:2008 certified facilities in Allen, Texas. Fairview Microwave is RF on-demand.

For additional information on this product, please click the following link: [N Directional Coupler 10 dB Coupled Port From 4 GHz to 8 GHz Rated To 50 Watts MC4052-10](https://www.fairviewmicrowave.com/n-directional-coupler-10-db-8-ghz-mc4052-10)

URL: <https://www.fairviewmicrowave.com/n-directional-coupler-10-db-8-ghz-mc4052-10-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Fairview Microwave reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal. Fairview Microwave does not make any representation or warranty regarding the suitability of the part described herein for any particular purpose, and Fairview Microwave does not assume any liability arising out of the use of any part or documentation.



<b>FAIRVIEW MICROWAVE INC.</b> ALLEN, TX 75013 WWW.FAIRVIEWMICROWAVE.COM		NOTES: 1. UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE NOMINAL. 2. ALL SPECIFICATIONS ARE SUBJECT TO CHANGE WITHOUT NOTICE AT ANY TIME. 3. DIMENSIONS ARE IN INCHES [mm].			
TITLE N Directional Coupler 10 dB Coupled Port From 4 GHz to 8 GHz Rated To 50 Watts		DWG NO MC4052-10		CAGE CODE 3FKR5	
CAD FILE	011415	SHEET	SCALE	N/A	SIZE A 5568