

Handheld IAQ Monitor

**Model 2212** 

**Multi-Function Indoor Air Quality Monitor** 

The Kanomax IAQ Monitor 2212 features quick start-up and high accuracy in measuring carbon dioxide and carbon monoxide concentration levels in the environment. Temperature and humidity are also simultaneously measured in a handy lightweight design.

## **Applications**

- IAQ Investigation
- Ventilation Testing
- Thermal Comfort Control
- Monitoring Toxic Gas

## *Features*

- Simultaneous measurements of CO, CO2, Temperature, and Relative humidity
- Calculates Dew point, Wet bulb temperature, Absolute humidity, Humidity Ratio, and % Outside Air
- Fast Relative Humidity response time, only 15 seconds
- Data HOLD, Record and recall MAX / MIN / AVG
- Store up to 1500 measurements
- Easy user self calibration
- PC interface with RS232C/USB and software for real-time measurements and downloading data to your PC
- Complete with probe with 79 in (2m) cable, probe stand, calibration cap & connection tube, data processing software, RS232C cable, Serial - USB converter, 6 pc. AA batteries, carrying case, and NIST-Traceable calibration certificate



## Handheld IAQ Monitor Model 2212 Specifications

Carbon Monoxide (CO)

Accuracy

Carbon Dioxide (CO2)

**Accuracy** 

**Temperature Ranges** 

Accuracy

**Relative Humidity Ranges** 

Accuracy

Interface

Datalogging

**Analog Output** 

**Power Supply** 

**Dimensions** 

Weight

0 to 500 ppm

+/- 3% of reading

0 to 5000 ppm

+/- 3% of reading

-4 to 140 °F (-20 to 60 °C)

+/- 1.0 °F (0.5 °C)

2.0 to 98.0 %RH

+/- 2% of reading

RS232C or USB

1500 measurements

0 to 1 V \*Option

6 x AA Batteries or AC Adapter

W3.4" x H7.4" x D1.6"

0.9 lbs (400 g)

Specifications are subject to change without notice.

Kanomax USA, Inc. P.O. Box 372 219 US Hwy 206, Andover, NJ 07821 U.S.A. TEL: 1-800-247-8887 (USA) / 1-973-786-6386 FAX: 1-973-786-7586 E-mail: info@kanomax-usa.com URL: www.kanomax-usa.com Distributed by: