

## About Trek: A Successful Company with Acknowledged Leadership Qualities

### Founded on Technology

TREK, INC. was established in 1968 to serve the needs of the electrophotography industry for highly accurate, stable, cost-effective measurement instrumentation and devices.



Novel probe design technology provided the foundation for the company's first electrostatic voltmeter, which quickly became the industry standard. Trek's design ensures highly accurate measurements under extreme conditions.

### Growth through Innovation

In the decades that followed, Trek established itself as a designer and manufacturer of high quality instrumentation.

Innovative designs and unique solutions have fueled product development over the years. Trek developed the world's first all-solid-state, high-voltage, high-speed, DC-stable amplifier, which is now the product of choice for medium-current ion implantation systems in semiconductor fabrication facilities around the world. As a result of Trek's close working relationship with its customers, new designs are constantly being created to answer the needs of industry and R&D.

### Technical Expertise and Application Knowledge

Our scientifically based measurement expertise, coupled with our application knowledge, has enabled us to establish an enviable position in the markets we serve.

We are the experts when it comes to highly accurate measurement instruments and high voltage amplifiers, and the technology that drives them. Customers can depend on Trek to understand both the technical and practical aspects of an application. In many cases Trek is viewed as a virtual member of the customer's product development team.

### Investing in the Future

In response to the needs of the marketplace, Trek recently established the Trek Technology Center in Lockport, NY as a facility for R&D and Engineering. In addition, a close working relationship with the nearby State University of New York at Buffalo assures that Trek has access to an extensive array of testing equipment and expertise to complement Trek's internal capabilities.



To enable future growth for the company, Trek's headquarters and manufacturing recently relocated to a refurbished 40,000 sq ft facility, also in Lockport.



### Dedicated to Excellence

Trek has a well-respected reputation for excellence. We are the premier resource for electrostatic measurement and high-voltage solutions due to our product leadership and engineering excellence.

### Committed to the Global Marketplace



Long before globalization was popular, TREK, INC. established Trek Japan KK in Tokyo, Japan for the purpose of providing sales, application engineering support and service to customers in Japan and elsewhere in the Pacific Rim region. A global sales and service network now exists enabling Trek to serve the needs of customers throughout the world.

Copyright © 2014 TREK, INC. 1417/JRB

## TREK - Experts in Electrostatic Measurement and High Voltage Power Amplifiers

TREK, INC. 190 Walnut Street • Lockport, NY 14094 • 800-FOR TREK  
716-438-7555 • 716-201-1804 (fax) • [www.trekinc.com](http://www.trekinc.com) • [sales@trekinc.com](mailto:sales@trekinc.com)



Measurement and Power Solutions™

[www.trekinc.com](http://www.trekinc.com)



# TREK, INC.

## Precision Measurement of Electrostatic Voltage Enabled by Trek Electrostatic Voltmeter Instruments

### Novel Probe Design

Trek is an expert in utilizing technology to enable the precise measurement of electrostatic voltage and was the pioneer in noncontacting measurement methods for the electrophotography industry. A novel approach to probe design provided the foundation for the company's first electrostatic voltmeter, which quickly became the industry standard. Trek voltmeters, both then and now, utilize a design that ensures highly accurate measurements under extreme conditions, differentiating them from other products in the marketplace.



Model 600B-7C Probe



Model 341B Electrostatic Voltmeter

### Capability Beyond Industry Norm

Trek's standard capabilities go well beyond the norm for others in this industry. What others call special, we call standard. Trek electrostatic voltmeters provide measurement ranges up to  $\pm 20$  kV, accuracies to the millivolt level, and speed of response to 50 microseconds for a 1 kV step. And Trek can go beyond what we call standard, to address application-specific requirements on a custom basis.

### Ideal for Critical Operations


Trek's electrostatic voltmeters are ideally suited for use in critical operations associated with electrophotography, semiconductor, LCD and other processes where voltages need to be precisely measured and controlled for process optimization, or where charge accumulation (and electrostatic discharge events) pose a threat to production yields or product quality. By placing Trek's instruments on-line within a process, real time feedback and control is possible.



Infitron® Model 820

### Performance in Diverse Applications

Trek noncontacting electrostatic voltmeter instruments are high performance devices that provide outstanding measurement speed and accuracy along with high surface resolution and no arc over. The voltmeter probes are designed to be less sensitive to dust particulates, enabling usage in diverse applications. Probe options include high temperature, high sensitivity, high resolution, transparent, miniature, and vacuum-friendly designs. Options also exist for probe aperture size, end/side view detection and body shape.



Model 370 Electrostatic Voltmeter

### Product Innovations for the Future

Trek's ultra-high impedance Infitron® voltmeter technology advances the state of the art, enabling precision and accuracy when an application requires surface contact measurements with virtually zero charge exchange upon probe contact. This need for site-specific contacting measurement is taking on a greater importance as electronics are miniaturized, and other critical surface phenomena are being scrutinized.



TREK, INC. • 190 Walnut Street • Lockport, NY 14094 • USA • 800-FOR TREK  
716-438-7555 • 716-201-1804 (fax) • [www.trekinc.com](http://www.trekinc.com) • [sales@trekinc.com](mailto:sales@trekinc.com)

# Electrostatic Voltmeter Selection Table

ESVM Model	Output Voltage Range (DC or peak AC)	Speed of Response (10-90%) (less than)	Voltage Monitor Output Accuracy (better than)	Probe Models (order separately unless otherwise noted)	Special Features	Typical Applications
<b>341B</b>	0 to ±20 kV	200 μs for a 1 kV step	±0.1% of full scale	3450 Standard 3453/3455 High-Temperature, High-Vacuum	High voltage, high speed	Electrostatic research & development, charge accumulation monitoring of LCD production processes, monitoring surface potentials in electrostatic painting processes, electrostatic potential measurement on polymers, rubber, fabrics & paper
<b>P0865</b>	0 to ±10 kV					
<b>370</b>	0 to ±3 kV	50 μs for a 1 kV step	±0.05% of full scale	3800 Miniature 3870 High-Speed 7000 Standard	Optional data acquisition module	Electrophotographic research & development, research & development of photoreceptors, charge accumulation monitoring in semiconductor production, measuring electrostatic potential on moving objects or surfaces, radiation effect studies
<b>370TR</b>	0 to ±3 kV	200 μs for a 1 kV step	±0.05% of full scale	3629A Transparent 3627 Standard	Transparent probe option	Photosensitive surface studies, research & development
<b>347</b>	0 to ±3 kV	3 ms for a 1 kV step	±0.05% of full scale	6000B Standard/High Res 555P Miniature 6300 High-Temperature	Wide variety of probe options	Photoconductor/dielectric surface voltage measurement, charge accumulation monitoring in semiconductor production, electrostatic potential measurement on film, polymers & paper
<b>344</b>	0 to ±2 kV	3 ms for a 1 kV step	±0.05% of full scale	6000B Standard/High Res 555P Miniature 6300 High-Temperature	Wide variety of probe options	Electrophotographic research & development, charge accumulation monitoring in semiconductor production, electrostatic potential measurement on film, polymers & paper
<b>368A</b>	0 to ±2 kV	200 μs for a 1 kV step	±0.1% of full scale	3800 Miniature 3870 High Speed	Multichannel enclosure	Research & development applications, electrostatic potential measurement on film, polymers & paper, electrophotographic research & development
<b>706B</b>	0 to +1 kV or 0 to -1 kV (switch selectable)	DPM Sampling Rate: 3 readings/second	±0.5% of full scale	Side Viewing Probe (included)	Portable, durable, battery operated	Photoreceptor evaluations, materials testing, static charge measurement for LCD, semiconductor, MR heads & IC processes
<b>323</b>	0 to ±100 V	300 ms for a 100 V step	±0.05% of full scale	6000B Standard/High Res 555P Miniature 6300 High-Temperature	High sensitivity (5 mV), response speed control, noise/speed adjustments	Semiconductor wafer surface voltage measurement, contact potential measurement, disk drive charge accumulation measurements
<b>320C</b>	0 to ±100 V	300 ms for a 100 V step	±0.05% of full scale	3250 High-Sensitivity	High sensitivity (1 mV), noise/speed adjustments	Materials evaluation, electret studies, contact potential measurement
<b>325</b>	0 to ±40 V	3 ms for a 10 V step	±0.05% of full scale	PD1216P High-Sensitivity	Low voltage, high sensitivity (1 mV), noise/speed adjustments	Materials evaluation, electret studies, contact potential measurement
<i>The electrostatic voltmeters listed above utilize Trek's noncontacting technology. Trek's new InfiniTron® technology permits contacting (and noncontacting) measurements with virtually zero charge transfer; refer to models below.</i>						
<b>800</b>	0 to ±100 V	3.5 ms for a 100 V step	±0.1% of full scale	800P Contacting/Noncontacting Probe (included)	InfiniTron® ultra-high impedance voltmeter: Resistance greater than 10 <sup>16</sup> Ω Capacitance less than 10 <sup>-15</sup> F	Measurement of ESD-sensitive components and circuitry where virtually zero charge transfer is required
<b>820</b>	0 to ±2 kV	500 μs for a 1 kV step	±0.1% of full scale	820P Contacting/Noncontacting Probe (included)	InfiniTron® ultra-high impedance voltmeter: Resistance greater than 10 <sup>15</sup> Ω Capacitance less than 10 <sup>-15</sup> F	Measurement of ESD-sensitive components and circuitry where virtually zero charge transfer is required
<b>821HH</b>	0 to ±2 kV	500 μs for a 1 kV step	±1% of full scale	821P Contacting/Noncontacting Probe (included)	InfiniTron® ultra-high impedance voltmeter: Resistance greater than 10 <sup>14</sup> Ω Capacitance less than 10 <sup>-14</sup> F	Hand-held unit for versatile measurement of ESD-sensitive components and circuitry where virtually zero charge transfer is required