

pH & Conductivity

The following pages contain a variety of instruments for the measurement of pH values as well as conductivity in microSiemens.

PHX 800 as a standard testing device for the pH values. TDS 3 as a standard testing device for microSiemens/cm².

For professional use one can select from the following range: PHT 810 pH meter instrument and PHT 830 pH meter, temperature compensated, with a variety of different electrodes, and the CT 830 conductivity measurement instrument, temperature compensated.



PHT 810
pH Meter



PHT 830
pH Meter



CT 830
Conductivity Meter



pH and
Conductivity
Standard Tester

The extended product range of  provides you with additional solutions for your major challenges in pH and conductivity measurement. For more information go to www.WTW.com.



pH and Conductivity Meter and Tester

Find your perfect meter:

Meter	Parameter	Measurement range	Probe type	Probe connection
PHT 810 pH Meter	pH	0 pH ... 14 pH	Various electrodes available	BNC
PHT 830 pH Meter	pH	0 pH ... 14 pH	pH-electrode with plastic shaft	Plug BK 6-pin
PHX 800 pH Tester	pH	0 pH ... 14 pH	Integrated electrode	–
CT 830 Conductivity Meter	Conductivity	0 ... 200 μ S, 0 ... 2000 μ S, 0 ... 20 mS, 0 ... 500 mS	Graphite electrode	Plug BK 6-pin
TDS 3 Conductivity Tester	Conductivity	0 ... 1,999 μ S, 0 ... 19.99 mS	Integrated electrode	–





PHT 810 pH Meter with automatic pH calibration



PHT 810



PHT 810 + AT 206



ST 1000



The device has been certified together with the EB 4401 food inspection case (please see page 155).

Technical Data

pH measurement range	0 pH ... 14 pH
pH measurement accuracy	0.03 pH
pH resolution	0.01 pH
Memory	Hold, MIN / MAX
Connector	BNC
Battery lifetime	Up to 5 years
Display	LCD, 12 mm
Operating temperature	0 °C ... +50 °C (+32 °F ... 122 °F)
Storage temperature	-25 °C ... +60 °C (-13 °F ... 140 °F)
Dimensions (L x W x H)	110 x 54 x 22 mm
Temperature compensation	Manual
Weight	Approximately 200 g
Certificate	2-point factory calibration certificate (included at pH meter set)

* Various electrodes available
(see p. 143)

- MIN/MAX and hold options
- Approximately 5 years battery life time

Type	Description	Part No.
PHT 810	pH Meter (without electrode*)	1340-5810
ST 1000	pH Meter Set (consisting of PHT 810, penetration electrode AT 206, punching pin, buffer solutions pH4 and pH7, carrying case)	1339-0620

Various electrodes for PHT 810

AT 200 plastic electrode

Housing material: plastic

Diameter: 12 mm

Shaft length: 120 mm



AT 201 laboratory electrode

Shaft housing material: glass

Shaft diameter: 12 mm

Shaft length: 900 mm



AT 206 penetration electrode

for measurements in semi-solid food products and other materials.

Housing material: glass

Shaft/electrode diameter:

25 mm/5 mm

Shaft/electrode length:

65 mm/12 mm

with 1m cable and BNC plug



Technical Data	AT 200	AT 201	AT 206
pH measurement range	0 pH ... 14 pH	0 pH ... 14 pH	2 pH ... 13 pH
Temperature measurement range	-5 °C ... +80 °C (+23 °F ... +176 °F)	-15 °C ... +130 °C (+5 °F ... +266 °F)	+5 °C ... +80 °C (+41 °F ... +176 °F)
Electrolyte	Gel	Gel	Referid®

Type	Description	Part No.
AT 200	Plastic electrode	1339-0631
AT 201	Measurement electrode for laboratories	1339-0632
AT 206	Penetration electrode	1339-0629

Accessories for PHT 810



AG 140 Protective cover for handheld devices, red



AT 100-PHT Carrying case



AT 400 Buffer solution pH 4



AT 401 Buffer solution pH 7



AT 405 KCl solution

Type	Description	Part No.
AG 140	Protective cover for handheld devices, red	1340-5005
AT 100-PHT	Carrying case	1340-5091
AT 400	Buffer solution pH 4	1341-3836
AT 401	Buffer solution pH 7	1341-3838
AT 405	KCl solution	1341-3839



PHT 830 pH Meter with auto range



PHT 830 SET 3

- Configuration directly on device using 5 buttons and display
- Graphic LCD display

Technical Data

Measurement range pH:	0 pH ... 14 pH
mV:	-1999 ... 1999 mV
Temperature:	-10 °C ... +100 °C
Resolution	0.01 pH; 1 mV; 0.1 °C
Temperature	-10 °C ... +100 °C
Display	128 x 64 Pixel, backlight
Interface	USB "Interface HMG USB"
Battery	3 Batteries Type AA, IEC R6, LR6, 1.5 V
Ambient	-10 °C ... +55 °C (+14 °F ... 131 °F)
Relative humidity	< 95% (non-condensing)
Connectors	Plug BK 6 pin (4 pin interface)
Housing	ABS plastic
Protection class	IP 65
Dimension (L x W x D)	200 x 95 x 40 mm
Weight	290 g

Type	Description	Part No.
PHT 830 SET 1	pH Meter with plastic electrode	1340-5812
PHT 830 SET 2	pH Meter with glass electrode	1340-5813
PHT 830 SET 3	pH Meter with penetration electrode	1340-5814

CT 830 Conductivity Meter with auto range



- Configuration directly on device using 5 buttons and display
- Graphic LCD display

Technical Data

Measurement range	0 ... 200 µS	TDS 0 ... 200 mg/l
	0 ... 2000 µS	TDS 0 ... 2000 mg/l
	0 ... 20 mS	TDS 0 ... 20 g/l
	0 ... 500 mS	TDS 0 ... 500 g/l
Temperature	-10 °C ... +100 °C	
Display	128 x 64 Pixel, backlight	
Interface	USB "Interface HMG USB"	
Battery	3 Batteries Type AA, IEC R6, LR6, 1.5 V	
Ambient	-10 °C ... +55 °C (+14 °F ... 131 °F)	
Relative humidity	< 95% (non-condensing)	
Connectors	Plug BK 6 pin (4 pin interface)	
Housing	ABS plastic	
Protection class	IP 65	
Dimension (L x W x D)	200 x 95 x 40 mm	
Weight	290 g	

Type	Description	Part No.
CT830 SET	Conductivity Meter	1340-5834

PHX 800 Basic pH Tester with acoustic signal



- Automatic deactivation
- Battery charge indicator
- Replaceable battery

Technical Data

pH measurement range	0 pH ... 14 pH
pH measurement accuracy	0.1 pH
pH resolution	±0.2 pH
Operating temperature	0 °C ... +50 °C (+32 °F ... 122 °F)
Storage temperature	-25 °C ... +60 °C (-13 °F ... 140 °F)
Housing material	ABS plastic
Dimension (L x W x H)	170 x 32 x 15 mm
Weight	Approximately 70 g
Battery	1.5 V A76/LR44
Battery lifetime	Approximately 150 hours
Deactivation	Automatically after 15 minutes

Type	Description	Part No.
PHX 800	Basic pH Tester	1340-5800

TDS 3 Basic Conductivity Tester Dual Display



- Battery charge indicator
- Replaceable battery

Technical Data

Measurement range	0 ... 1,999 µS	0 ... 1,999 ppm
	0 ... 19.99 mS	0 ... 19.99 ppt
Measurement accuracy	1 µS	
Resolution	1 µS	
Operating temperature	0 °C ... +50 °C (+32 °F ... 122 °F)	
Storage temperature	-25 °C ... +60 °C (-13 °F ... 140 °F)	
Housing material	ABS plastic	
Dimension (L x W x H)	170 x 32 x 15 mm	
Weight	Approximately 70 g	
Battery	4 x 1.5 V A76/LR44	
Battery lifetime	Approximately 150 hours	

Type	Description	Part No.
TDS 3	Basic Conductivity Tester	1340-5831