



GD-3300

Combustible Gas Leak Detector 16" inch Gooseneck detector is easy to measure the hard-reached areas. Highly sensitive and reliable Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak. Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate. Pinpoint small Leaks: Detects all combustible gas leaks even tiny leaks.



Features	
16" inch Gooseneck detector is easy to measure the hard-reached areas.	
Highly sensitive and reliable	
Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.	
Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.	
Pinpoint small Leaks: Detects all combustible gas leaks even tiny leaks.	

Pump driven field adjustable range	10ppm
Sensor Type	Solid State
Alarm	Visible & Audible at 10% LEL for Methane. Can be calibrated for other concentrations or gases.
Warm-Up	Approx. 1 minute
Response Time	Less than 2 sec. (up to 40% LEL)
Duty Cycle	Intermittent
Probe Length	16"
Battery	3 "C" Alkaline



CE

Combustible Gas Leak Detector

16" inch Gooseneck detector is easy to measure the hard-reached areas.
 Highly sensitive and reliable
 Easy to Use: One-hand operation with thumb controlled tick adjust knob. Tick accelerates when sensor tip approaches leak.
 Use in contaminated Environments: Eliminates background gas concentration with fully adjustable tick rate.
 Pinpoint small Leaks: Detects all combustible gas leaks even tiny leaks.



GAS Detectors



ALARM
>90 dB



16" inch Gooseneck detector



High quality Sensor




Accessories:

Batteries and Gift box with carrying case.